

# TI2007-047

## Inline NATO Receptacle to DC Aviation Plug, 2' Cable Assembly



**Power Anytime, Anywhere**

The Tesla™ Inline NATO Receptacle to DC Aviation Plug is constructed from a rugged combination of advanced composite materials and corrosion-resistant alloys, and features Tesla's Inline NATO receptacle. The result is a weatherproof NATO receptacle assembly that will withstand the harshest battlefield conditions and other extreme environments.

### Features:

- Rated to 3000 peak amps
- UV, fuel, fungus, oil, and water resistant
- Tested to withstand 50 G of shock
- Exceeds MIL-STD-810F
- Manufactured by Tesla™
- 2' 1Ø Cable
- 2 Year Warranty



**Tesla™** Industries, Inc.

[www.teslainsd.com](http://www.teslainsd.com) ♦ [www.tesla1.com](http://www.tesla1.com)

Email: [tesla1@teslainsd.com](mailto:tesla1@teslainsd.com)

**Headquarters:** (302) 324-8910

101 Centerpoint Blvd. New Castle, DE 19720

**Western Regional Office:** (775) 622-8801


9475 Double R Blvd. Suite 2, Reno, NV 89521



**The POWER  
Of  
RED™**



# Components and Technical Specifications



<b>Technical Specifications:</b>	
Rated Voltage	18 - 32 Vdc
Inrush Current (@ 28 Vdc)	3000 A
Rated Current	1500 A
Peak Current	3000 A
Storage Temperature	-65 °C - 125 °C (-85 °F - 257 °F)
Operating Temperature	-40 °C - 110 °C (-40 °F - 230 °F)
Air Gap-leakage Path	0.200" (5 mm)
Protection Class	IP28C
Cable Length	2'
Weight	6.76 (3.01 kg)
Warranty	2 years (3 years optional)

